

# HSM VK 4812P

## Channel baling press HSM VK 4812 P

For industrial applications with small material loads - Troughput up to approx. 204 m<sup>3</sup>/h



### Technical data

<b>Order number:</b>	6460001	<b>Loading aperture width x Loading aperture length:</b>	1020 x 1250 mm
<b>Pressing power:</b>	480 kN	<b>Bale width x Bale height x Bale length:</b>	1100 x 750 x 600-1200 mm
<b>Specific pressing power:</b>	58,2 N/cm <sup>2</sup>	<b>Length x Width x Height:</b>	6661 x 3994 x 2583 mm
<b>Driving power:</b>	22 kW	<b>Weight:</b>	10 t
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Type of consumables:</b>	Wire
<b>Cycle time when idling vacío:</b>	18,2 s	<b>Press material:</b>	Plastic film, Mixed paper, Cardboard, Punch waste/residue, PET
<b>Volume throughput in idle operation (theor.):</b>	204 m <sup>3</sup> /h		
<b>Volume throughput at 50kg/m<sup>3</sup> (theor.):</b>	10.2 t/h		

### Product information



Particularly suitable for compression of PET bottles



Versatile solution for materials up to approx. 60 kg /m<sup>3</sup> bulk weight



Very low space requirement thanks to compact and sturdy design