



HSM V-Press 860 plus B

HSM V-Press 860 plus B vertical baling press

With a pressing power of 594 kN and low-noise and energysaving technology, the HSM V-Press 860 plus B is the most economical and ecological solution for your waste disposal.

Technical data

Order number:	6058214	Bale length x Bale width x Bale height:	1500 x 1200 x 780 mm
EAN	4026631080064	Bale weight:	550 kg
Pressing power:	594 kN	Method of loading:	manual
Specific pressing power:	50,76 N/cm ²	Width x Depth x Height:	2099 x 1245 x 2985 mm
Driving power:	4 kW	Weight:	2340 kg
Voltage / Frequency:	400 V / 50 Hz	Related product line:	V-Press
Cycle time when idling vac�o:	25 s	Type of consumables:	Wire, Pre-looped wire
Volume throughput in idle operation (theor.):	32,5 m ³ /h	Press material:	Plastic film, Cardboard
Loading height:	1129 mm		
Loading aperture width x height:	1500 x 651 mm		

Product information



Produces particularly large, high density bales which can be sold with no further compression required



To fill the press, the upper half of the doors is pushed down and automatically opens after the compression process



Hand wheel door lock - Easy to handle thanks to counter-rotating thread for quick opening and closing



Compresses cardboard and film

Suitable for cardboard as well as film.



Automatic start

Automatic start of the pressing process after closing the door.



Economical, fast and silent

The HSM V-Presses are highly energy efficient thanks to the specially developed rapid stroke technology. This saves time and money.




Graphic-capable display

Convenient membrane keypad with text display, which shows the current status of the machine.




HSM TCS

HSM TCS (TorsionControlSystem) for monitoring press ram movement.



Strapping

Strapping with wire – optional tape station available for strapping with polyester tape or wire according to requirements.



www.tuev-sued.de/ps-zert



www.hsm.eu

HSM®