



HSM VK 6015

Kanalballenpresse HSM HSM VK 6015

Für Industrieanwendungen mit speziellen Anforderungen - Durchsatz bis ca. 291 m³/h

Product information

Available as an option with frequency-regulated drive – saves 40 % of the energy used by standard drives




Particularly suitable for compression of paper, cardboard, plastic film, production remains, e.g. trimmings from a variety of materials



Programmable Siemens logic controller with touch panel



Optimally adjusted software for different materials guarantees high bale quality even when material is frequently changed



Technical data

Order number:	6442002	Length x Width x Height:	10500 x 3770 x 3260 mm
Pressing power:	720 kN	Weight:	20 t
Specific pressing power:	128 N/cm ²	Method of strapping:	horizontal
Driving power:	55 kW □ [45kW frequency-controlled]	Number of strappings:	4
Voltage / Frequency:	400 V / 50 Hz	Type of consumables:	Wire
Cycle time when idling vacío:	13,2 s	Industry type:	Recycling & Disposal, Logistics & Distribution, Retail, Food & beverage industry, Industry & Manufacturing, Print & Packaging
Volume throughput in idle operation (theor.):	231 m ³ /h	Press material:	PET bottles, aluminium beverage cans, soft packaging, Punch waste/residue, HDPE / LDPE hollow containers & plastic bottles, Big Bags, PET beverage and aluminium cans, soft packaging, Cardboard, Mixed paper, Plastic film
Volume throughput at 50kg/m³ (theor.):	11.55 t/h	Use for product line:	VK
Loading aperture width x Loading aperture length:	620 x 1500 mm		
Bale width x Bale height x Bale length:	750 x 750 x 600-2000 mm		
Bale weight:	260-470 kg		