

# HSM Powerline SP 4040 V - 5.8 mm



## HSM Powerline SP 4040 V shredder baler combination

This compact combination of the FA 400.2 heavy duty document shredder and a vertical baling press is designed for the professional destruction of large quantities of documents, which are then compressed into bales of up to 35 kg.

### Technical data

<b>Order number:</b>	2513111144	<b>Intake width:</b>	428 mm
<b>EAN</b>	4026631060226	<b>Bale width x Bale height x Bale length:</b>	600 x 500 x 400 mm
<b>Cutting type:</b>	strip cut	<b>Bale weight:</b>	35 kg
<b>Security level (DIN 66399):</b>	E-2   O-2   P-2   T-2	<b>Width x Depth x Height:</b>	1117 x 2175 x 1981 mm
<b>Cutting capacity in sheets 80g/m<sup>2</sup>:</b>	104	<b>Weight:</b>	737 kg
<b>Pressing power:</b>	44 kN	<b>Shredder material:</b>	Paper, Staples and paper clips, Credit card, CD/DVD, Crumpled paper, Floppy disk, Computer listings
<b>Driving power:</b>	6,2 kW		
<b>Voltage / Frequency:</b>	400 V / 50 Hz		

### Product information



The material feeding is convenient and takes place via the non-slip conveyor belt.



The removal trolley allows for the easy removal and disposal of the compact bales.



To ensure a consistently high cutting capacity, shredder baler combinations with cross cut have a manual oiler.

# HSM®



### Specially hardened solid steel cutting rollers

The induction-hardened solid steel cutting rollers are wear-resistant and guarantee durability.



### Continuous operation

Powerful drive allows continuous operation.



### Compression into boxes or waste bag

The shredded material which has been compressed into compact bales can be cleanly disposed of either in a box (HSM SP 4040 V) or a waste bag (HSM SP 4040 V, HSM SP 5080). These prevent particles from falling out and ensure clean handling.



### Bale weight can be manually set

The bale weight is variable and depends on your requirement (HSM SP 5080, HSM SP 5088).



### User safety through emergency off switch

It may be necessary to stop the machine immediately so we have equipped the device with an emergency off switch.



### Dust extractor

The powerful and energy efficient dust extractor HSM DE 4-100 in dust classification M ensures an optimal extraction due to the high air flow volume, thereby reducing dust emissions (accessory).



\*HSM Powerline SP 5080 / SP 5088

