

HSM Powerline SP 5088 - 6 x 40-53 mm

HSM Powerline SP 5088 shredder baler combination

With this waste disposal station, HSM combines the FA 500.3 heavy duty document shredder with a channel baling press. It is therefore perfect for use in archives or central stations for shredding large quantities of documents, which are then compressed into bales of up to 90 kg.

Technical data

Order number:	2990414134	Intake width:	500 mm
EAN	4026631060301	Bale width x Bale height	500 x 500 x 400-950 mm
Cutting type:	particle cut	x Bale length:	
Security level (DIN 66399):	E-2 O-2 P-3 T-3	Bale weight:	90 kg
		Width x Depth x Height:	1273 x 3281 x 1792 mm
Cutting capacity in sheets 80g/m²:	300 - 350	Weight:	1660 kg
		Related product line:	Powerline
Pressing power:	85 kN		
		Shredder material:	Paper, Staples and paper clips, Credit card, CD/DVD, Folders, USB sticks, Crumpled paper, Floppy
Driving power:	11,5 kW		
Voltage / Frequency:	400 V / 50 Hz		
			disk, Computer listings

Product information



The material feeding is convenient and takes place via the non-slip conveyor belt.



We have integrated an automatic oiler into the device which will ensure it runs smoothly, giving you a consistently high cutting capacity and quality.



The combination can be commissioned very easily using Plug-and-Play. The conveyor beltshredder can therefore be combined with a press at any time.





Specially hardened solid steel cutting rollers

The induction-hardened solid steel cutting rollers are wear-resistant and guarantee durability.



Continuous operation

Powerful drive allows continuous operation.



Compression shredded material

Shredded material is compressed into compact bales, which are manually tied off with three baler straps and can also be disposed of cleanly in a waste bag.



Bale weight can be manually set

The bale weight is variable and depends on your requirement (HSM SP 5080, HSM SP 5088).



User safety through emergency off switch

It may be necessary to stop the machine immediately so we have equipped the device with an emergency off switch.



Dust extractor

The powerful and energy efficient dust extractor HSM DE 4-75 in dust classification M ensures an optimal extraction due to the high air flow volume, thereby reducing dust emissions (accessory).



*HSM Powerline SP 5080 / SP 5088



