

HSM Pure 120




Aktenvernichter HSM Pure 120

Datenschutz beginnt am Schreibtisch. Der kompakte Papier-Aktenvernichter schreddert personalisierte Werbung, Korrespondenz aller Art, Quittungen und Zahlbelege zuverlässig und sicher.

Technical data

Order number:	2313111	Container volume / collecting:	20 l
EAN	4026631054461	Collection volume in sheets (80 g):	184
Cutting type:	particle cut	Noise level (idle operation):	ca. 55 - 60 dB(A)
Cutting size:	4 x 25 mm	Width x Depth x Height:	366 x 258 x 415 mm
Security level (DIN 66399):	E-3 F-1 P-4 T-4	Weight:	4,5 kg
Cutting capacity in sheets 80g/m²:	5 - 6	Related product line:	Pure
Power consumption:	160 W	Shredder material:	Paper, Staples and paper clips, Credit card
Voltage / Frequency:	220-240 V / 50 Hz/60 Hz		
Intake width:	225 mm		

Product information



The hardened steel cutting rollers with a lifetime warranty can easily cope with staples and paper clips and guarantee durability.



To empty the waste container, the housing top can be easily removed – a practical, recessed grip facilitates handling.



The high quality materials and proven HSM "Made in Germany" quality guarantee you are receiving a safe and durable machine.

HSM®



Quiet operation

The quiet operating mode minimises noise development in the workplace which is an important consideration for your staff.



Low power consumption

The stand-by and automatic switch-off features ensure a high degree of energy saving when the shredder is not in use.



Anti-paper jam function

The paper feed with overload protection reduces paper jams and sustains the high throughput of paper.



High level of user safety

User safety is paramount. A slight pressure on the safety element immediately stops the paper feed and prevents unintentional entry into the machine.



Automatic start/stop

The operation is very easy: the device starts automatically when fed with paper and automatically stops after shredding is complete.



Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).



* Nicht für / not for HSM Pure 320

