



HSM VK 15020

Channel baling press HSM VK 15020

For professional disposal management or larger industrial applications with high throughput rates - Throughput up to approx. 873 m³/h

Product information

Available as an option with frequency-regulated drive – saves 40 % of the energy used by standard drives



Suitable for cardboard, plastic film and compressing DSD goods, UBC as well as PET bottles (other materials on request)



Solid steel construction with highly wear resistant steel parts inside the press chamber and press channel



Solid steel construction with extremely wear-resistant, replaceable steel



Technical data

Order number:	6438004	Length x Width x Height:	12900 x 4160 x 3910 mm
Pressing power:	1500 kN	Weight:	45 t
Specific pressing power:	124 N/cm ²	Method of strapping:	horizontal
Driving power:	75+75 kW frequency-controlled	Number of strappings:	5
Voltage / Frequency:	400 V / 50 Hz	Type of consumables:	Wire
Cycle time when idling vacío:	10 s	Industry type:	Retail, Recycling & Disposal, Logistics & Distribution, Industry & Manufacturing, Print & Packaging
Volume throughput in idle operation (theor.):	873 m ³ /h	Press material:	Punch waste/residue, Big Bags, Plastic film, Mixed paper, Cardboard, HDPE / LDPE hollow containers & plastic bottles
Volume throughput at 50kg/m³ (theor.):	43.65 t/h	Use for product line:	VK
Loading aperture width x Loading aperture length:	970 x 2000 mm		
Bale width x Bale height x Bale length:	1100 x 1100 x 600-2000 mm		
Bale weight:	800-1250 kg		