

HSM VK 4812P



Channel baling press HSM VK 4812 P

For industrial applications with small material loads - Troughput up to approx. 204 m³/h

Product information

Particularly suitable for compression of PET bottles



Integration into automated industrial production processes



Operating side can be selected



Suitable for continuous loading with conveyor belt, air feeding or similar



Technical data

Order number:	6450001	Length x Width x Height:	7700 x 3750 x 2400 mm
Pressing power:	480 kN	Weight:	10 t
Specific pressing power:	58,2 N/cm ²	Method of strapping:	horizontal
Driving power:	22 kW	Number of strappings:	4
Voltage / Frequency:	400 V / 50 Hz	Type of consumables:	Wire
Cycle time when idling vacío:	18,2 s	Industry type:	Logistics & Distribution, Food & beverage industry, Industry & Manufacturing, Print & Packaging, Retail
Volume throughput in idle operation (theor.):	204 m ³ /h	Press material:	Punch waste/residue, PET bottles, aluminium beverage cans, soft packaging, Cardboard, Mixed paper, Plastic film, PET beverage and aluminium cans, soft packaging
Volume throughput at 50kg/m³ (theor.):	10.2 t/h	Use for product line:	VK
Loading aperture width x Loading aperture length:	1020 x 1250 mm		
Bale width x Bale height x Bale length:	1100 x 750 x 600-1200 mm		
Bale weight:	300-500 kg		