



HSM VK 8818

Channel baling press HSM VK 8818

For professional disposal management or larger industrial applications with high throughput rates - Throughput up to approx. 643 m³/h

Product information

Available as an option with frequency-regulated drive – saves 40 % of the energy used by standard drives



Suitable for cardboard, plastic film and compressing DSD goods, UBC as well as PET bottles (other materials on request)



Available as an option suitable for residual waste (with wear-resistant steel)



Gimballed press cylinder system - Reduced wear on the pressing cylinder and press ram guides



Technical data

Order number:	6429004	Length x Width x Height:	11900 x 3870 x 3700 mm
Pressing power:	880 kN	Weight:	33 t
Specific pressing power:	106,7 N/cm ²	Method of strapping:	horizontal
Driving power:	75 kW	Number of strappings:	5
Voltage / Frequency:	400 V / 50 Hz	Type of consumables:	Wire
Cycle time when idling vacío:	12,8 s	Industry type:	Retail, Recycling & Disposal, Logistics & Distribution, Industry & Manufacturing, Print & Packaging
Volume throughput in idle operation (theor.):	418 m ³ /h	Press material:	Big Bags, HDPE / LDPE hollow containers & plastic bottles, Plastic film, Mixed paper, Cardboard, Punch waste/residue
Volume throughput at 50kg/m³ (theor.):	20.9 t/h	Use for product line:	VK
Loading aperture width x Loading aperture length:	970 x 1800 mm		
Bale width x Bale height x Bale length:	1100 x 750 x 600-2000 mm		
Bale weight:	500-700 kg		