HSM VK 4812

Channel baling press HSM VK 4812

For industrial applications with small material loads - Troughput up to approx. 332 m³/h

Technical data

Order number:	6400001
Pressing power:	480 kN
Specific pressing power:	58,2 N/cm²
Driving power:	22 kW
Voltage / Frequency:	400 V / 50 Hz
Cycle time when idling vacío:	18,2 s
Volume throughput in idle operation (theor.):	204 m³/h
Volume throughput at 50kg/m³ (theor.):	10.2 t/h

Loading aperture width x Loading aperture length:	1020 x 1250 mm
Bale width x Bale height x Bale length:	1100 x 750 x 600-1200 mm
Length x Width x Height:	7456 x 2570 x 2583 mm
Weight:	10 t
Type of consumables:	Wire
Press material:	Plastic film, Mixed paper, Cardboard, Punch waste/residue

Product information

Fully automatic vertical strapping

Versatile solution for materials up to approx. 60 kg /m³ bulk weight

With large loading aperture and higher pressing power

System solution

Integration into automated industrial production processes.

Continuous loading

Suitable for continuous loading with conveyor belt, air feeding or similar.

Optimized pressing

High bale density and high bale weights.

Automatic operation

Control of the pressing process via light barrier.

Operating side

Can be fully integrated into existing workflows and processes. Operating side can be selected.

Variety of uses

Suitable for almost all requirements. Contact us if you have other materials or applications. We will find you a suitable solution.

Made in Germany