



# HSM VK 4812

## Channel baling press HSM VK 4812

For industrial applications with small material loads - Troughput up to approx. 332 m³/h

### Product information

Particularly suitable for compression of cardboard and plastic film



Integration into automated industrial production processes



Operating side can be selected



Suitable for continuous loading with conveyor belt, air feeding or similar



## Technical data

<b>Order number:</b>	6649002	<b>Length x Width x Height:</b>	7700 x 3750 x 2400 mm
<b>Pressing power:</b>	480 kN	<b>Weight:</b>	10 t
<b>Specific pressing power:</b>	58,2 N/cm <sup>2</sup>	<b>Method of strapping:</b>	horizontal
<b>Driving power:</b>	30 kW	<b>Number of strappings:</b>	4
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Type of consumables:</b>	Wire
<b>Cycle time when idling vacío:</b>	11,2 s	<b>Industry type:</b>	Print & Packaging, Retail, Logistics & Distribution, Industry & Manufacturing
<b>Volume throughput in idle operation (theor.):</b>	332 m <sup>3</sup> /h	<b>Press material:</b>	Punch waste/residue, Cardboard, Mixed paper, Plastic film
<b>Volume throughput at 50kg/m<sup>3</sup> (theor.):</b>	16.6 t/h	<b>Use for product line:</b>	VK
<b>Loading aperture width x Loading aperture length:</b>	1020 x 1250 mm		
<b>Bale width x Bale height x Bale length:</b>	1100 x 750 x 600-1200 mm		
<b>Bale weight:</b>	300-500 kg		