



# HSM VK 6215

## Channel baling press HSM VK 6215

For professional disposal management or larger industrial applications with high throughput rates - Throughput up to approx. 540 m³/h

### Product information

Available as an option with frequency-regulated drive – saves 40 % of the energy used by standard drives



Suitable for cardboard, plastic film and compressing DSD goods, UBC as well as PET bottles (other materials on request)



Available as an option suitable for residual waste (with wear-resistant steel)



Solid press carriage guidance with easy maintenance access



## Technical data

<b>Order number:</b>	6443005	<b>Length x Width x Height:</b>	10000 x 3990 x 3000 mm
<b>Pressing power:</b>	620 kN	<b>Weight:</b>	24 t
<b>Specific pressing power:</b>	75,2 N/cm <sup>2</sup>	<b>Method of strapping:</b>	horizontal
<b>Driving power:</b>	55 kW frequency-controlled	<b>Number of strappings:</b>	5
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Type of consumables:</b>	Wire
<b>Cycle time when idling vacío:</b>	8,3 s	<b>Industry type:</b>	Recycling & Disposal, Retail, Print & Packaging, Industry & Manufacturing, Logistics & Distribution
<b>Volume throughput in idle operation (theor.):</b>	540 m <sup>3</sup> /h	<b>Press material:</b>	HDPE / LDPE hollow containers & plastic bottles, Big Bags, Punch waste/residue, Cardboard, Mixed paper, Plastic film
<b>Volume throughput at 50kg/m<sup>3</sup> (theor.):</b>	27.0 t/h	<b>Use for product line:</b>	VK
<b>Loading aperture width x Loading aperture length:</b>	970 x 1500 mm		
<b>Bale width x Bale height x Bale length:</b>	1100 x 750 x 600-2000 mm		
<b>Bale weight:</b>	300-550 kg		