

HSM SECURIO B35 - 1 x 5 mm



HSM SECURIO B35 document shredder

For more data security in the workplace. The excellent document shredder with an intake width of 400 mm for professional data destruction in an open-plan office for up to eight people.

Technical data

Order number:	1924111	Container volume / collecting:	130 l
EAN	4026631044257	Collection volume in sheets (80 g):	2340
Cutting type:	particle cut	Noise level (idle operation):	ca. 56 dB(A)
Cutting size:	1 x 5 mm	Width x Depth x Height:	620 x 525 x 870 mm
Security level (DIN 66399):	F-3 P-7	Weight:	53,7 kg
Cutting capacity in sheets 80g/m²:	5	Related product line:	SECURIO
Power consumption:	700 W	Shredder material:	Paper
Voltage / Frequency:	220-240 V / 50 Hz		
Intake width:	400 mm		

Product information



The induction-hardened, solid steel cutting rollers guarantee durability.



Reusable cardboard box as bin for shredded material.



After opening the door, the reusable collecting bag can be easily removed and emptied.



For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



Energy-saving

In stand-by mode, intelligent control programme EcoSmart ensures there is an exceptionally low power consumption of 0.1 watts.



High level of user safety

The safety element prevents unintentional entry of materials into the machine and thereby increases the user safety.



Automatic start/stop

The operation is very easy: the device starts automatically when fed paper and automatically stops after shredding is complete.



Anti-paper jam function

The paper feed with overload protection reduces paper jams and sustains the high throughput of paper.



Convenient emptying

Robust wooden cabinet with castors. After opening the door, the reusable collecting bag can be easily removed and emptied.



5 year warranty on the HSM SECURIO B-series document shredders in security levels P-2 to P-5 according to ISO/IEC 21964 (DIN 66399). 3 year warranty on all other HSM SECURIO document shredders. Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).

