

# HSM HL 3521 T



## HSM HL 3521 T horizontal baling press

The model HSM HL 3521 T can be filled via conveyor and is especially designed to compact tyres. Of course, other packaging materials can also be compressed.

### Product information

Hydraulic loading flap for maximum operating comfort and for precompressing



Hydraulic counterplate for bale removal ensures optimum operating convenience and safety



Stored-program controller PLC



Feeding: manual or automatic



## Technical data

<b>Order number:</b>	6270000	<b>Length x Width x Height:</b>	7900 x 1660 x 2485 mm
<b>Pressing power:</b>	320 kN	<b>Weight:</b>	8100 kg
<b>Specific pressing power:</b>	40 N/cm <sup>2</sup>	<b>Method of strapping:</b>	horizontal
<b>Driving power:</b>	22 kW	<b>Number of strappings:</b>	5
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Type of consumables:</b>	Wire
<b>Cycle time when idling vacío:</b>	44 s	<b>Industry type:</b>	Recycling & Disposal, Logistics & Distribution, Food & beverage industry, Industry & Manufacturing, Print & Packaging
<b>Volume throughput in idle operation (theor.):</b>	137 m <sup>3</sup> /h	<b>Press material:</b>	Polystyrene, Big Bags, Tyres, Cardboard, Mixed paper, Plastic film
<b>Loading aperture width x Loading aperture length:</b>	800 x 2100 mm	<b>Use for product line:</b>	HL
<b>Bale width x Bale height x Bale length:</b>	800 x 1000 x 1200 mm		
<b>Bale weight (up to):</b>	850 kg		
<b>Method of loading:</b>	manual		