

# HSM Powerline SP 5080 - 10.5 x 40-76 mm



## HSM Powerline SP 5080 shredder baler combination

This powerful combination of the FA 500.3 heavy duty document shredder and a counterplate baling press provides for data security in archives and compresses the shredded material into bales of between 40 and 80 kg.

### Technical data

<b>Order number:</b>	2992209134	<b>Intake width:</b>	500 mm
<b>EAN</b>	4026631060257	<b>Bale width x Bale height x Bale length:</b>	570 x 490 x 800 mm
<b>Cutting type:</b>	particle cut	<b>Bale weight:</b>	80 kg
<b>Security level (DIN 66399):</b>	E-2   O-2   P-2   T-2	<b>Width x Depth x Height:</b>	1267 x 2474 x 1792 mm
<b>Cutting capacity in sheets 80g/m²:</b>	510 - 550	<b>Weight:</b>	1350 kg
<b>Pressing power:</b>	80 kN	<b>Related product line:</b>	Powerline
<b>Driving power:</b>	11,5 kW	<b>Shredder material:</b>	Paper, Staples and paper clips, Credit card, CD/DVD, Folders, USB sticks, Crumpled paper, Floppy disk, Computer listings
<b>Voltage / Frequency:</b>	400 V / 50 Hz		

### Product information



The material feeding is convenient and takes place via the non-slip conveyor belt.



We have integrated an automatic oiler into the device which will ensure it runs smoothly, giving you a consistently high cutting capacity and quality.



The combination can be commissioned very easily using Plug-and-Play. The conveyor belt-shredder can therefore be combined with a press at any time.

# HSM®



### Specially hardened solid steel cutting rollers

The induction-hardened solid steel cutting rollers are wear-resistant and guarantee durability.



### Continuous operation

Powerful drive allows continuous operation.



### Compression into boxes or waste bag

The shredded material which has been compressed into compact bales can be cleanly disposed of either in a box (HSM SP 4040 V) or a waste bag (HSM SP 4040 V, HSM SP 5080). These prevent particles from falling out and ensure clean handling.



### Bale weight can be manually set

The bale weight is variable and depends on your requirement (HSM SP 5080, HSM SP 5088).



### User safety through emergency off switch

It may be necessary to stop the machine immediately so we have equipped the device with an emergency off switch.



### Dust extractor

The powerful and energy efficient dust extractor HSM DE 4-75 in dust classification M ensures an optimal extraction due to the high air flow volume, thereby reducing dust emissions (accessory).



\*

\*HSM Powerline SP 5080 / SP 5088



[www.hsm.eu](http://www.hsm.eu)

**HSM®**