

## Dust extractor HSM DE 4-100 - FA 500.3/SP 5080/SP 5088

## HSM DE 4-100 dust extractor

The powerful and energy efficient dust extractor in dust classification M ensures an optimal extraction due to the high air flow volume, thereby reducing dust emissions. The model is suitable for connection to the HSM Powerline FA 400.2 and FA 500.3 heavy duty document shredders as well as HSM Powerline SP 4040 V, SP 5080 and SP 5088 shredder baler combinations.

## **Technical data**

Order number:	2411114	Max. volume flow:	2000 m³/h
EAN	4026631070843	Filter area:	10 m²
Driving power:	2,2 kW	Dust classification:	Μ
Voltage / Frequency:	400 V / 50 Hz	<b>Related product line:</b>	Powerline
Container volume / collecting:	42	Use for device type:	SP 5088, FA 500.3, SP 5080
Width x Depth x Height:	1460 x 935 x 1440 mm		
Max. negative pressure:	2600 Pa		

## **Product information**



The use of high quality materials combined with HSM's proven "Made in Germany" high manufacturing standard ensures that the product is both safe and durable for the user.



The dust extractor meets the requirements of dust classification M.



Due to the fully automatic filter cleaning, the dust extractor can be operated continuously.

