



HSM HL 4809 ST

HSM HL 4809 horizontal baling press

This very compact, horizontal working counter plate press is suitable for large disposal tasks in retail and in small to medium central storages. The HL 4809 ST produces bales with a cross-section of 1100 x 750 mm and a weight of up to 430 kg. The integrated hydraulic lifting/tilting device significantly reduces the number of people required to compact the recycling material.

Technical data

| | | | |
|--|-------------------------|--|--|
| Order number: | 6423304 | Bale width x Bale height x Bale length: | 1100 x 750 x 1200 mm |
| EAN | 4026631065405 | Bale weight: | 420 kg |
| Pressing power: | 480 kN | Method of loading: | Lifting/tilting system, wire mesh cart |
| Specific pressing power: | 58 N/cm ² | Length x Width x Height: | 5926 x 1978 x 2042 mm |
| Driving power: | 11 kW | Weight: | 5900 kg |
| Voltage / Frequency: | 400 V / 50 Hz | Type of consumables: | Wire |
| Cycle time when idling vacío: | 35 s | Press material: | Plastic film, Mixed paper, Cardboard |
| Volume throughput in idle operation (theor.): | 32,81 m ³ /h | | |
| Loading aperture width x Loading aperture length: | 1020 x 900 mm | | |


Product information



Suitable for cardboard as well as film



Convenient and particularly fast loading via hydraulic lifting/tilting device



Also available as a variant with automatic start



Sturdy design

Very low space requirement thanks to compact and sturdy design.



Display and PLC

Multilingual operational guidance and Stored-program controller PLC.



Efficient truck loading

Optimised bale dimensions and bale weights for efficient truck loading.



Sliding door

Hydraulic sliding door for bale removal ensures optimum operating convenience and safety.



Pallet locking mechanism

Pallet locking mechanism for safe bale removal.



Strapping

Manual bale strapping with Quick-link wire.

