

HSM VK 5012



Product information

Operating side can be selected



Suitable for cardboard, plastic film and compressing DSD goods, UBC as well as PET bottles (other materials on request)



Solid steel construction with highly wear resistant steel parts inside the press chamber and press channel



Solid steel construction with extremely wear-resistant, replaceable steel



Technical data

Order number:	6451003	Bale weight:	300-550 kg
Pressing power:	500 kN	Length x Width x Height:	8990 x 3990 x 3000 mm
Specific pressing power:	60,6 N/cm ²	Weight:	20 t
Driving power:	45 kW	Method of strapping:	horizontal
Voltage / Frequency:	400 V / 50 Hz	Number of strappings:	4
Cycle time when idling vacío:	8,4 s	Industry type:	Recycling & Disposal, Retail, Logistics & Distribution, Industry & Manufacturing, Print & Packaging
Volume throughput in idle operation (theor.):	442 m ³ /h	Press material:	Punch waste/residue, Plastic film, Mixed paper, Cardboard, HDPE / LDPE hollow containers & plastic bottles, Big Bags
Volume throughput at 50kg/m³ (theor.):	22.1 t/h	Use for product line:	VK
Loading aperture width x Loading aperture length:	1020 x 1250 mm		
Bale width x Bale height x Bale length:	1100 x 750 x 600-1200 mm		