



HSM VK 3008

Channel baling press HSM VK 3008

For industrial applications with small material loads - Troughput up to approx. 197 m³/h

Product information

Particularly suitable for compression of paper, cardboard and plastic film



Integration into automated industrial production processes



Operating side can be selected



Für kontinuierliche Beschickung mit Förderband, Luftbeschickung o. ä. geeignet

Technical data

Order number:	6644001	Length x Width x Height:	6100 x 2350 x 2130 mm
Pressing power:	310 kN	Weight:	6,3 t
Specific pressing power:	55,4 N/cm ²	Method of strapping:	horizontal
Driving power:	22 kW	Number of strappings:	4
Voltage / Frequency:	400 V / 50 Hz	Type of consumables:	Wire
Cycle time when idling vacío:	8,2 s	Industry type:	Logistics & Distribution, Retail, Industry & Manufacturing, Print & Packaging
Volume throughput in idle operation (theor.):	197 m ³ /h	Press material:	Cardboard, Mixed paper, Plastic film
Volume throughput at 50kg/m³ (theor.):	9.85 t/h	Use for product line:	VK
Loading aperture width x Loading aperture length:	620 x 800 mm		
Bale width x Bale height x Bale length:	700 x 800 x 600-1200 mm		
Bale weight:	190-350 kg		