HSM VK 3008

Channel baling press HSM VK 3008

For industrial applications with small material loads - Troughput up to approx. 197 m³/h

Technical data

Order number:	6644001
Pressing power:	310 kN
Specific pressing power:	55,4 N/cm²
Driving power:	22 kW
Voltage / Frequency:	400 V / 50 Hz
Cycle time when idling vacío:	8,2 s
Volume throughput in idle operation (theor.):	197 m³/h
Volume throughput at 50kg/m³ (theor.):	9.85 t/h

Loading aperture width x Loading aperture length:	620 x 800 mm
Bale width x Bale height x Bale length:	700 x 800 x 600-1200 mm
Length x Width x Height:	6498 x 2951 x 2030 mm
Weight:	6,3 t
Type of consumables:	Wire
Press material:	Plastic film, Mixed paper, Cardboard

Product information

Particularly suitable for compression of paper, cardboard and plastic film

Versatile solution for materials up to approx. 50 kg /m³ bulk weight

Fast cycle times, 800 mm loading aperture

System solution

Integration into automated industrial production processes.

Continuous loading

Suitable for continuous loading with conveyor belt, air feeding or similar.

Optimized pressing

High bale density and high bale weights.

Automatic operation

Control of the pressing process via light barrier.

Operating side

Can be fully integrated into existing workflows and processes. Operating side can be selected.

Variety of uses

Suitable for almost all requirements. Contact us if you have other materials or applications. We will find you a suitable solution.

Made in Germany