



# HSM VK 3012

## Channel baling press HSM VK 3012

For industrial applications with small material loads - Troughput up to approx. 228 m<sup>3</sup>/h

### Product information

Particularly suitable for compression of paper, cardboard and plastic film



Integration into automated industrial production processes



Operating side can be selected



Für kontinuierliche Beschickung mit Förderband, Luftbeschickung o. ä. geeignet

## Technical data

<b>Order number:</b>	6645001	<b>Length x Width x Height:</b>	6700 x 2350 x 2130 mm
<b>Pressing power:</b>	310 kN	<b>Weight:</b>	6,3 t
<b>Specific pressing power:</b>	55,4 N/cm <sup>2</sup>	<b>Method of strapping:</b>	horizontal
<b>Driving power:</b>	22 kW	<b>Number of strappings:</b>	4
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Type of consumables:</b>	Wire
<b>Cycle time when idling vacío:</b>	10,1 s	<b>Industry type:</b>	Logistics & Distribution, Retail, Industry & Manufacturing, Print & Packaging
<b>Volume throughput in idle operation (theor.):</b>	228 m <sup>3</sup> /h	<b>Press material:</b>	Cardboard, Mixed paper, Plastic film
<b>Volume throughput at 50kg/m<sup>3</sup> (theor.):</b>	11.4 t/h	<b>Use for product line:</b>	VK
<b>Loading aperture width x Loading aperture length:</b>	620 x 1140 mm		
<b>Bale width x Bale height x Bale length:</b>	700 x 800 x 600-1200 mm		
<b>Bale weight:</b>	190-350 kg		