



HSM VK 4212

Kanalballenpresse HSM VK 4212

Für Industrieanwendungen mit kleinem bis mittlerem Materialaufkommen - Durchsatz bis ca. 251 m³/h

Technical data

Order number:	6647000	Loading aperture width x Loading aperture length:	620 x 1140 mm
Pressing power:	420 kN	Bale width x Bale height x Bale length:	700 x 800 x 600-1200 mm
Specific pressing power:	75 N/cm²	Length x Width x Height:	7378 x 2882 x 2030 mm
Driving power:	15 kW	Weight:	6,3 t
Voltage / Frequency:	400 V / 50 Hz	Type of consumables:	Wire
Cycle time when idling vacío:	17,4 s	Press material:	Plastic film, Mixed paper, Cardboard, Punch waste/residue
Volume throughput in idle operation (theor.):	132 m³/h		
Volume throughput at 50kg/m³ (theor.):	6.6 t/h		

Product information



Suitable for compressing paper, cardboard, shredded material and plastic film



Versatile solution for materials up to approx. 60 kg /m³ bulk weight



With large loading aperture for optimised feeding methods (1140 mm length)



System solution

Integration into automated industrial production processes.



Continuous loading

Suitable for continuous loading with conveyor belt, air feeding or similar.



Optimized pressing

High bale density and high bale weights.



Automatic operation

Control of the pressing process via light barrier.



Operating side

Can be fully integrated into existing workflows and processes. Operating side can be selected.



Variety of uses

Suitable for almost all requirements. Contact us if you have other materials or applications. We will find you a suitable solution.

