



# HSM VK 4212

## Channel baling press HSM VK 4212

For industrial applications with small material loads - Troughput up to approx. 251 m<sup>3</sup>/h

### Product information

Integration into automated industrial production processes



Suitable for compressing paper, cardboard, shredded material and plastic film



Operating side can be selected



Suitable for continuous loading with conveyor belt, air feeding or similar



## Technical data

<b>Order number:</b>	6647002	<b>Length x Width x Height:</b>	7200 x 2350 x 2130 mm
<b>Pressing power:</b>	420 kN	<b>Weight:</b>	6,3 t
<b>Specific pressing power:</b>	75 N/cm <sup>2</sup>	<b>Method of strapping:</b>	horizontal
<b>Driving power:</b>	30 kW	<b>Number of strappings:</b>	4
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Type of consumables:</b>	Wire
<b>Cycle time when idling vacío:</b>	9,2 s	<b>Industry type:</b>	Logistics & Distribution, Industry & Manufacturing, Print & Packaging, Retail
<b>Volume throughput in idle operation (theor.):</b>	251 m <sup>3</sup> /h	<b>Press material:</b>	Cardboard, Punch waste/residue, Plastic film, Mixed paper
<b>Volume throughput at 50kg/m<sup>3</sup> (theor.):</b>	12.55 t/h	<b>Use for product line:</b>	VK
<b>Loading aperture width x Loading aperture length:</b>	620 x 1140 mm		
<b>Bale width x Bale height x Bale length:</b>	700 x 800 x 600-1200 mm		
<b>Bale weight:</b>	220-420 kg		