



## HSM VK 4208

### Channel baling press HSM VK 4208

For industrial applications with small material loads - Troughput up to approx. 216 m³/h

#### Technical data

<b>Order number:</b>	6646001	<b>Loading aperture width x Loading aperture length:</b>	620 x 800 mm
<b>Pressing power:</b>	420 kN	<b>Bale width x Bale height x Bale length:</b>	700 x 800 x 600-1200 mm
<b>Specific pressing power:</b>	75 N/cm²	<b>Length x Width x Height:</b>	6960 x 2882 x 2030 mm
<b>Driving power:</b>	30 kW	<b>Weight:</b>	6,3 t
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Type of consumables:</b>	Wire
<b>Cycle time when idling vacío:</b>	7,5 s	<b>Press material:</b>	Plastic film, Mixed paper, Cardboard, Punch waste/residue
<b>Volume throughput in idle operation (theor.):</b>	216 m³/h		
<b>Volume throughput at 50kg/m³ (theor.):</b>	10.8 t/h		

#### Product information



Suitable for compressing paper, cardboard, shredded material and plastic film



Versatile solution for materials up to approx. 60 kg /m³ bulk weight



Fast cycle times, 800 mm loading aperture



### System solution

Integration into automated industrial production processes.



### Continuous loading

Suitable for continuous loading with conveyor belt, air feeding or similar.



### Optimized pressing

High bale density and high bale weights.



### Automatic operation

Control of the pressing process via light barrier.



### Operating side

Can be fully integrated into existing workflows and processes. Operating side can be selected.



### Variety of uses

Suitable for almost all requirements. Contact us if you have other materials or applications. We will find you a suitable solution.

