



# HSM V-Press 503 eco

## HSM V-Press 503 vertical baling press eco

Easy installation and operation make the HSM V-press 503 eco as the ideal model for small material volumes.

### Product information

To fill the press, the upper half of the doors is swung to the right



Bell-crank lever for quick and safe opening of the door



Bale removal and transport with discharge trolley



Automatic start of the pressing process after closing the door



## Technical data

<b>Order number:</b>	6154104	<b>Width x Depth x Height:</b>	953 x 679 x 1962 mm
<b>EAN</b>	4026631073387	<b>Weight:</b>	245 kg
<b>Pressing power:</b>	30 kN	<b>Number of strappings:</b>	2
<b>Specific pressing power:</b>	8,5 N/cm <sup>2</sup>	<b>Type of consumables:</b>	Strapping tape
<b>Voltage / Frequency:</b>	230 V / 50 Hz	<b>Industry type:</b>	Logistics & Distribution, Retail, Industry & Manufacturing, Print & Packaging
<b>Cycle time when idling vacío:</b>	30 s		
<b>Volume throughput in idle operation (theor.):</b>	3,13 m <sup>3</sup> /h	<b>Press material:</b>	Plastic film, Mixed paper, Cardboard
<b>Loading aperture width x height:</b>	700 x 505 mm		
<b>Bale length x Bale width x Bale height:</b>	700 x 500 x 850 mm		