



## HSM VK 2306

### Channel baling press HSM VK 2306

For industrial applications with small material loads - Troughput up to approx. 121 m<sup>3</sup>/h

#### Product information

Compresses paper, cardboard, plastic film and PET bottles



Particularly suitable for PET compaction and for special applications



Operating side can be selected



Suitable for continuous loading with conveyor belt, air feeding or similar



## Technical data

<b>Order number:</b>	6651002	<b>Bale weight:</b>	140-250 kg
<b>Pressing power:</b>	240 kN	<b>Length x Width x Height:</b>	5295 x 2863 x 1565 mm
<b>Specific pressing power:</b>	64 N/cm <sup>2</sup>	<b>Weight:</b>	3,5 t
<b>Driving power:</b>	15 kW	<b>Method of strapping:</b>	horizontal
<b>Voltage / Frequency:</b>	400 V / 50 Hz	<b>Number of strappings:</b>	3
<b>Cycle time when idling:</b>	6,7 s	<b>Type of consumables:</b>	Wire
<b>Volume throughput in idle operation (theor.):</b>	121 m <sup>3</sup> /h	<b>Industry type:</b>	Logistics & Distribution, Food & beverage industry, Industry & Manufacturing, Print & Packaging, Retail
<b>Volume throughput at 50kg/m<sup>3</sup> (theor.):</b>	6.05 t/h	<b>Press material:</b>	PET beverage and aluminium cans, soft packaging, Punch waste/residue, PET, Cardboard, Mixed paper, Plastic film
<b>Loading aperture width x Loading aperture length:</b>	670 x 600 mm		
<b>Bale width x Bale height x Bale length:</b>	750 x 500 x 600-1200 mm		