

HSM ProfiPack P425

This powerful device perforates several layers of used cardboard into packaging material. The clever solution for all shipping and storage areas.

Technical data

Order number:	1531154	EAN:	4026631062596
Throughput capacity:	80 kg/h	Noise level (idle operation):	ca. 60 - 62 dB(A)
Voltage / Frequency:	220-240 V / 50-60 Hz	Intake width:	425 mm
Infeed height:	20 mm	Power consumption:	2000 W
Width x Depth x Height:	770 x 611 x 1040 mm	Machine weight:	160 kg

Product Information:



The packaging material can be used wherever required and provides an optimum protection for objects.



The intuitive operator control panel with LED indicators on a robust keypad signals the operating status of the device.



The efficient drive concept ensures a powerful operation at constant load.



The high efficiency of the drive contributes to the device's low energy consumption.



The device can be used on a mobile basis and has smooth-running, stable castors with a parking brake.



When the emergency stop switch is actuated, the device stops immediately.



The infinitely variable adjustment of the working width with a scale allows the production of cushioning material exactly as required.



Depending on the application, the cushioning volume of the packaging material can be adjusted as required.



The induction-hardened solid steel cutting rollers are wear-resistant against cardboard staples and guarantee durability.

Made in Germany

quiet operation

www.hsm.eu