



HSM ProfiPack P425 + adapter set for dust extractor

This robust and performance-optimised packaging machine is used to process a number of layers of cardboard into a padding mat or padded filling material. The professional device is mobile on steering rollers and can be used with total flexibility.

Technical data

Order number:	1533054	EAN:	4026631072724
Throughput capacity:	120 kg/h	Noise level (idle operation):	ca. 63 - 64 dB(A)
Voltage / Frequency:	400 V / 50 Hz	Intake width:	425 mm
Infeed height:	20 mm	Power consumption:	3800 W
Width x Depth x Height:	770 x 611 x 1040 mm	Machine weight:	186 kg

Product Information:



Integrated connection for dust suction (dust extractor optionally available).



The packaging material can be used wherever required and provides an optimum protection for objects.



The user can adjust the feed-in speed exactly as required.



The efficient drive concept ensures a powerful operation at constant load.



The high efficiency of the drive enables a particularly sustainable operation of the device.



When the emergency stop switch is actuated, the device stops immediately.



The infinitely variable adjustment of the working width with a scale allows the production of cushioning material exactly as required.



Depending on the application, the cushioning volume of the packaging material can be adjusted as required.



The induction-hardened solid steel cutting rollers are wear-resistant against cardboard staples and guarantee durability.



The intuitive operator control panel with LED indicators on a robust keypad signals the operating status of the device.