



V-Press 860 eco 460001163

used electro-hydraulic baling press model HSM V-Press 860 eco
with double door stop hand right sight / handwheel door lock
incl. operating manual and declaration of conformity

- year of construction 2015
- wire strapping

Technical details

- Dimensions W 1797 x D 1070 x H 2990 mm
- Weight approx. 1889 kg
- Motor 4,0 kW
- Voltage / Frequency 3 x 400 V / 50 Hz
- Pressing power 548 kN
- Cycle time in idle operation 25 sec.
- Hourly output approx. 1 - 2 bales
- Bale weight approx. 300 kg
(depending on material)
- Max. bale size
L 1200 x W 780 x H 1000-1200 mm
- Keypad with selectable program for cardboard
and foil and graphic capable display of respective current
status, bale counter and working hour meter
- Auto-start and stop when door is opened
or closed
- TorsionControlSystem (TCS)
- Semi-automatic 4-fold strapping with eyelet wire
- Basic equipment: 2 coils wire 2.8x3700mm

You need the following electrical connection:
CEE-plug 3x16 A+N+PE6h, fuse protection 16 A,
circuit breaker trait K or C

technical and optical modifications reserved
product image is an example image

delivery time: on demand

Modifications and errors reserved/used electro-hydraulic baling press
model HSM V-Press 860 eco
with double door stop hand right sight / handwheel door lock
incl. operating manual and declaration of conformity

- year of construction
- wire strapping

Technical details

- Dimensions W 1797 x D 1070 x H 2990 mm
- Weight approx. 1889 kg
- Motor 4,0 kW
- Voltage / Frequency 3 x 400 V / 50 Hz
- Pressing power 548 kN
- Cycle time in idle operation 25 sec.



- Hourly output approx. 1 - 2 bales
- Bale weight approx. 300 kg
(depending on material)
- Max. bale size
L 1200 x W 780 x H 1000-1200 mm
- Keypad with selectable program for cardboard and foil and graphic capable display of respective current status, bale counter and working hour meter
- Auto-start and stop when door is opened or closed
- TorsionControlSystem (TCS)
- Semi-automatic 4-fold strapping with eyelet wire
- Basic equipment: 2 coils wire 2.8x3700mm

You need the following electrical connection:
CEE-plug 3x16 A+N+PE6h, fuse protection 16 A,
circuit breaker trait K or C

technical and optical modifications reserved
product image is an example image

delivery time: on demand

Modifications and errors reserved

Caractéristiques

Réf. d'article :	6148167G04680	Standort:	Allemagne
Pression de compactage spécifique:	584 kN	Type de produit:	Presses à balles verticales
Tension / Fréquence:	400 V / 50 Hz		
Poids:	1900 kg		