



## HL 7009 Li, 400V/50Hz 530003570

refurbished Semi-automatic, electro-hydraulic counterplate-press

- left hand operation
- with hydraulic lifting-tilting device
- /incl. operating manual and Declaration of Conformity

- year of manufacture 2017
- wire strapping

### \*Technical Data

- Motor power 9,2 + 1,5 kW
- Voltage / Frequency 3 x 400 V / 50 Hz
- Pressing power 700 kN
- Specific pressing power 58 N/cm<sup>2</sup>
- Cycle time (press stroke in idle operation moving forward and return) approx. 46,00 s
- Cycle time (partial stroke), 32,5 sec
- Pump capacity 55,8 l/min
- Tank content 123 l
- Loading aperture (W x L) 1020 x 900 mm
- Maximum bale size L 1100x W 1100 x H appr. 1200 mm
- Bale weight (supermarket cardboard) 1.04 (B19) up to 600 kg, bale length approx. 1200 mm
- Space requirements including handling area and pallet (L x W x H) 5790 x 2899 x 2975 mm
- Keypad with electable programmes for cardboard <(>&<)> foil and Graphics display showing Status quo, bale counter and working hour meter
- Manual 4 – times strapping with quick – link – wire
- Initial equipment: 3 bundles wire 2,45 x 4400 mm

The following power connection is needed:

Rated current I<sub>n</sub>: 19 A

Total fuse: 3 x 32 A gG/gL/D-characteristic

Plug connection: CEE 32 A 3 P+N+PE

Length of the supply cable: Standard = 7,5 m

### Technical description HSM HL 7009

- Feeding via hydraulic lifting-tilting device
- Fully automatic compression
- horizontal 4-fold-strapping with Quick-Link-Wire
- Control of press intervals via light-barrier
- Operating side on left hand side, seen in compression direction
- HSM stored program controller incl. bale counter and service-mode
- Removal of bales by Euro-pallet carrier laterally or from the front
- Paintwork standard:  
Baling Press RAL 7035 (light grey)
- Basic machine weight without accessories approx. 7,7 t

**HSM**®

- Inclusive technical documentation
- Inclusive GS-label and CE-label (declaration of conformity CE / EEC)

Initial equipment included in delivery:

- initial filling with hydraulic oil
- initial equipped with 3 coils of quick-link-wire

technical and optical modifications reserved  
product image is an example image

delivery time: on demand

## Specificaties

<b>Productnr.:</b>	6335134G03883	<b>Standort:</b>	Polen
<b>Perskracht:</b>	700 kN	<b>Producttype:</b>	Horizontale balenpersen
<b>Spanning / Frequentie:</b>	400 V / 50 Hz		
<b>Gewicht:</b>	8500 kg		