



## V-Press 825 Plus 490001272

used Electro-hydraulic baling press model HSM V-Press 825 Plus  
Loading flap (fixed at the bottom) and handwheel door lock  
/incl. operating instruction and declaration of conformity

- year of construction 2016
- tape strapping

### Technical details

- Motor 4.0 kW
- Voltage / Frequency 3 x 400 V / 50 Hz
- Pressing power 250 kN
- Hourly output approx. 2 - 5 bales
- Bale weight up to 280 kg  
(depending on material)
- Max. bale size  
L 1200 x W 780 x H 700 mm
- Dimensions W 1700 x D 1046 x H 2370 mm
- Weight approx. 1063 kg
- Keypad with selectable program for cardboard  
and foil  
and graphic capable display of respective current status,  
bale counter and working hour meter
- Auto-start and stop when door is opened  
or closed
- TorsionControlSystem (TCS)
- Manual 4-fold strapping with polyester tape

You need the following electrical connection:  
CEE-plug 3x16 A+N+PE6h, fuse protection 16 A,  
circuit breaker trait K or C,  
or fuses trait gl

technical and optical modifications reserved  
Product image is an example image

Delivery date: on demand

Modifications and errors reserved/used Electro-hydraulic baling press  
model HSM V-press 825 plus  
Loading flap (fixed at the bottom) and handwheel door lock  
incl. operating instruction and declaration of conformity

- year of construction 2015
- tape strapping

### Technical details

- Motor 4.0 kW
- Voltage / Frequency 3 x 400 V / 50 Hz
- Pressing power 250 kN
- Hourly output approx. 2 - 5 bales
- Bale weight up to 280 kg  
(depending on material)



- Max. bale size  
L 1200 x W 780 x H 700 mm
- Dimensions W 1700 x D 1046 x H 2370 mm
- Weight approx. 1063 kg
- Keypad with selectable program for cardboard and foil  
and graphic capable display of respective current status,  
bale counter and working hour meter
- Auto-start and stop when door is opened or closed
- TorsionControlSystem (TCS)
- Manual 4-fold strapping with polyester tape

You need the following electrical connection:  
CEE-plug 3x16 A+N+PE6h, fuse protection 16 A,  
circuit breaker trait K or C, or fuses trait gl

technical and optical modifications reserved  
product image is an example image

delivery time: on demand

Modifications and errors reserved

## Спецификации

<b>Номер товара:</b>	6152244G04782	<b>Вес:</b>	1063 kg
<b>Presskraft:</b>	250 kN	<b>Standort:</b>	Германия
<b>Напряжение / Частота:</b>	400 V / 50 Hz		